

BA3 Series

100 A 600 V; shallow

Product specifications



- Conductor range: 6–2 AWG
Neutral Conductor Range: 1/0–14 AWG
Ground Conductor Range: 2–14 AWG
- Aluminum tunnel type connectors for both load and line sides
- For overhead, underground and combination overhead/underground

- Supplied with screw type ring
- Weatherproof Type 3R enclosure

Note: Supply from an underground network often requires use of stud type connector. Consult your local utility.



Approved for copper or aluminum

	Cat. no.	Description	Dimensions (in.)			Weight each		
			H	W	D	lb	kg	
	4 Jaw							
	BA3-V	Overhead, hub opening	9¼	7⅞	3⅜	5	2.2	
	BA3-INV	Overhead opening comes with insulated neutral	9¼	7⅞	3⅜	5	2.2	
	BA3-1V	Overhead, hub opening, comes with 1 in. hub	9¼	7⅞	3⅜	5	2.2	
	BA3-1 1/4V	Overhead, hub opening, comes with 1¼ in. hub	9¼	7⅞	3⅜	5	2.2	
	BA3-1 1/4INV	Overhead , hub opening comes with 1¼ in. hub and insulated neutral	9¼	7⅞	3⅜	5	2.2	
	BA3-TV	Underground	9¼	7⅞	3⅜	5	2.2	
	BA3-INTV	Underground come with insulated neutral	9¼	7⅞	3⅜	5	2.2	
	BA3-TCV	Combination overhead-underground	9¼	7⅞	3⅜	5	2.2	
		BA3-INTCV	combination overhead-underground come with insulated neutral	9¼	7⅞	3⅜	5	2.2
BA33-V		Overhead, twin hub opening	9¼	7⅞	3⅜	5	2.2	
BA33-INV		Overhead , twin hub opening come with insulated neutral	9¼	7⅞	3⅜	5	2.2	
BA33-1V		Overhead, twin hub opening comes with 1 in. hubs	9¼	7⅞	3⅜	5	2.2	
BA33-1 1/4V		Overhead, twin hub opening, comes with 1¼ in. hubs	9¼	7⅞	3⅜	5	2.2	
BA4-V*		Indoor type, KO on top	9¼	7⅞	3⅜	5	2.2	
BA4-INV*		Indoor type, KO on top, comes with insulated neutral	9¼	7⅞	3⅜	5	2.2	
BA4-VGN*		Indoor type, KO on top, comes with ground lug on neutral	9¼	7⅞	3⅜	5	2.2	
Factory-installed accessories								
Include: -5			5 th jaw, standard capacity, 9 o'clock position					
*for indoor use only unit is not NEMA 3R								

Diagrams

