

Covers

Straight Cover Number Selection

(ALUW12)SNC-3			
Material Prefix	Width	Bottom Type	Length
ALUW • Aluminum SPW • Pregalvanized SHW • Hot-dipped galvanized after fabrication SSW • Stainless steel 316	06 • (6 in.) 12 • (12 in.) 18 • (18 in.) 24 • (24 in.) 30 • (30 in.) 36 • (36 in.)	SNC • Solid non-flanged cover SFC • Solid flanged cover VFC • Ventilated flanged cover PFC • Peaked flanged cover PVC • Peaked ventilated cover	3 • (3 meters)

* For SHW covers, maximum lengths are 72 in. and 1500 mm.

Fitting Cover Number Selection

(ALUW12)SNCHB9024					
Material Prefix	Width	Cover Type	Fitting Type	Degree*	Radius
ALUW • Aluminum SPW • Pregalvanized SHW • Hot-dipped galvanized after fabrication SSW • Stainless steel 316	06 • (6 in.) 12 • (12 in.) 18 • (18 in.) 24 • (24 in.) 30 • (30 in.) 36 • (36 in.)	SNC • Solid non-flanged cover SFC • Solid flanged cover VFC • Ventilated flanged cover	HB • Horizontal bend HT • Horizontal tee HX • Horizontal cross VI • Vertical inside bend VTU • Vertical tee down HYR • Horizontal wye right HYL • Horizontal wye left	30 • (30°) 45 • (45°) 60 • (60°) 90 • (90°)	12 • (12 in.) 24 • (24 in.) 36 • (36 in.)

Note: Cover mounting hardware sold separately.

* Required for HB & VI only

Covers

Fitting Cover Number Selection (cont'd)

(ALUW1812)SNCRT12

Material Prefix	Width 1	Width 2	Cover Type	Fitting Type	Radius*
ALUW • Aluminum SPW • Pregalvanized SHW • Hot-dipped galvanized after fabrication SSW • Stainless steel 316	06 • (6 in.) 12 • (12 in.) 18 • (18 in.) 24 • (24 in.) 30 • (30 in.) 36 • (36 in.)	06 • (6 in.) 12 • (12 in.) 18 • (18 in.) 24 • (24 in.) 30 • (30 in.) 36 • (36 in.)	SNC • Solid non-flanged cover SFC • Solid flanged cover VFC • Ventilated flanged cover	RT • Horizontal reduce tee ET • Horizontal expand tee EX • Horizontal expand cross HSR • Horizontal straight reducer HLR • Horizontal left reducer HRR • Horizontal right reducer	12 • (12 in.) 24 • (24 in.) 36 • (36 in.)

* Radius not required for HSR, HLR, HRR

Fitting Cover Number Selection

(ALUW312)SNCVO9024

Material Prefix	Side Rail Height	Width	Cover Type	Fitting Type	Degree*	Radius
ALUW • Aluminum SPW • Pregalvanized SHW • Hot-dipped galvanized after fabrication SSW • Stainless steel 316	2 • (2 in.) 3 • (3-5/8 in.) 6 • (6 in.)	06 • (6 in.) 12 • (12 in.) 18 • (18 in.) 24 • (24 in.) 30 • (30 in.) 36 • (36 in.)	SNC • Solid non-flanged cover SFC • Solid flanged cover VFC • Ventilated flanged cover	VO • Vertical outside bend VTD • Vertical tee down CS • Cable support	30 • (30°) 45 • (45°) 60 • (60°) 90 • (90°)	12 • (12 in.) 24 • (24 in.) 36 • (36 in.)


Note: Cover mounting hardware sold separately.

* Required for VO only

Covers

Accessories for Covers

Hold Down Clamp




Designed to secure cable tray to support system.

Cat. No.	Material Prefix	Side Rail Height
(Prefix)-2-HDC	SPUW SSUW SHUW	2
(Prefix)-3-HDC		3
(Prefix)-6-HDC		6

Covers

Accessories for Covers

Cover Clamp



Rigid cover clamp for flat and flanged covers.

Cat. No.	Material Prefix	Side Rail Height
(Prefix)-2-SCC	SPUW SSUW	2
(Prefix)-3-SCC	SPW SSW	3
(Prefix)-6-SCC		6

Heavy-Duty Cover Clamp



Cat. No.	Material Prefix	Side Rail Height	Tray Width (in.)
(Prefix)-2-**-HCC	ALUW SHUW SPUW SSUW	2	6 12 18
(Prefix)-3-**-HCC	ALUW SHW SPW SSW	3	24 30 36
(Prefix)-6-**-HCC		6	

** Insert tray width