

## Barrier Strips

### Barrier Strips



Barrier Strips provide a method of separating cables in tray and trough systems. Easily installed using supplied hardware or barrier strip clamps (sold separately).

72 in. Barriers are flexible for use with horizontal fittings.

NOTE: Barriers provided with self drilling-tapping screw  
 CAT. NO. SPW10SCR  
 72 in. length: 3 screw  
 3 m length: 5 screw  
 144 in. length: 6 screw

Cat. No.	Material Prefix	Designed for Side Rail Height (in.)	Length
(Prefix)-3-SBH-72 (Prefix)-4-SBH-72 (Prefix)-5-SBH-72 (Prefix)-6-SBH-72 (Prefix)-7-SBH-72	SPW SHW SSW	3	72 in.
		4	
		5	
		6	
		7	
(Prefix)-3-SB-(*) (Prefix)-4-SB-(*) (Prefix)-5-SB-(*) (Prefix)-6-SB-(*) (Prefix)-7-SB-(*)	SPW SHW SSW	3	144 in. 3 m
		4	
		5	
		6	
		7	

Note: SHW barriers are only available in 72 in. or 1500 mm. (\*) Insert length.

### Inside/Outside Vertical Bend Barriers




Preformed to fit all standard steel vertical bends.

Provided with hardware.

Inside Bend Cat. No.	Outside Bend Cat. No.	Material Prefix	Designed for Side Rail Height (in.)
(Prefix)-3-VIB-(*)-(+)	(Prefix)-3-VOB-(*)-(+)	SPW SHW SSW	3
(Prefix)-4-VIB-(*)-(+)	(Prefix)-4-VOB-(*)-(+)		4
(Prefix)-5-VIB-(*)-(+)	(Prefix)-5-VOB-(*)-(+)		5
(Prefix)-6-VIB-(*)-(+)	(Prefix)-6-VOB-(*)-(+)		6
(Prefix)-7-VIB-(*)-(+)	(Prefix)-7-VOB-(*)-(+)		7

(\*) Insert bend degree (+) Insert bend radius.


### Barrier Strip Clamp



Barrier strip clamps mount barrier strips to ladder rungs and ventilated trough bottoms. Complete mounting hardware supplied.

Cat. No.	Material Prefix
(Prefix)-BSC	SPW SSW

### Barrier Strip Splice



Cat. No.	Material Prefix
ABW-BSS	SPW SSW

Alignment splice for joining connecting barrier strips.