Max-Gard interconnection systems

Dimensions


Male plug

Amp	A (in.)	B (in.)
30	43/4	71/8
60	5 ½	91/8
100	6½	101/8
200	9	133/4
400	12 5 /e	175/8


Connector

Amp	A (in.)	B (in.)
30	83/4	5 1 /8
60	10	53/8
100	11½	53/8
200	15	91/2
400	191/8	103/4

Diagram*



Diagram*



Male inlet


Amp	A (in.)	B (in.)	C (in.)
30	21/8	21/2	5½
60	33/8	2½	5½
100	33/8	21/2	5½
200	51/4	31/2	91/4
400	35/8	43/8	91/4

Receptacle with angle enclosure

Amp	A (in.)	B (in.)	C (in.)
30	63/s	3 1 /8	97/8
60	7½	4	11½
100	7½	4	113/8
200	_	_	_
400	_	_	_

Diagram

Diagram



A A B C

^{*} Flap covers shown – Screw covers available. On all, screw covers have nominal effect on outside dimensions.

Max-Gard interconnection systems

Dimensions


Receptacle with angle adapter and DJB junction box

		I	Dimensions (in.)
Amp	A (in.)	B (in.)	C (in.)
30	91/8	3	95/8
60	101/2	3	93/4
100	103/4	33/4	10
200	15¾	65/8	145/8
400	251/4	12	203/4


Receptacle with angle adapter

	Dimensions (in.)	
Amp	A (in.)	B (in.)
30	61/8	95/8
60	7½	93/4
100	7	10
200	91/2	143/4
400	131/4	20¾

Diagram*




Diagram*



Receptacle only

		Dimensions (in.)
Amp	A (in.)	B (in.)
30	21/8	41/2
60	33/8	51/8
100	35∕8	53%
200	51/4	65/8
400	7	71/8

Diagram



^{*} Flap covers shown screw covers available. On all, screw covers have nominal effect on outside dimensions.