













Technical specifications

Technical specifications












Configuration	Type	Ind. wire gauge size (AWG)	Width range (in.)	Rating range (amperes)	Comments
Extra-flexible links for heavy-duty application					
	FBEXA	36	1½–1¾	350–1,000	Extra-flexible 1-hole NEMA Boreal's top of the line
	FBEXB	36	1½–1¾	400–2,000	Extra-flexible 2-hole NEMA Boreal's top of the line
	FBEXG	36	1¾–2	900–1,650	Extra-flexible transformer link
	FBEXH	36	3–4	1,400–4,000*	Extra-flexible 4-hole NEMA Boreal's top of the line
	FBEXJ	36	3¼–3¾	2,300–3,600*	Extra-flexible 90° 4-hole NEMA Boreal's top of the line
Standard flexible links for medium-duty application					
	FBB**-1 FBC**-1 FBD**-1	30	1¼–1¾	350–1,000	NEMA std. grounding connectors
	FBD** FB2D** FB3D** FBXD** FB2XD**	30	1½–1¾	400–2,000	Same as FBEXB with 30 AWG wires
	FBSWB	30	1½–2	700–1,750	Standard transformer link
	FBSWC	30	3	1,300–2,350	Same construction as SWB with different hole pattern
	FBSWC	30	3	1,300–2,350	4 hole pads also available in wider configuration, refer to EXH, SWD and LTL series
	FBSWC	30	3	1,300–2,350	Same construction as SWC Type A with different hole configuration
	FBSWC	30	3	1,300–2,350	Same construction as SWC Type A with different hole configuration

* For ampacity over 2,500 please contact your inside sale representative

** Specify desired length.

Technical specifications

Technical specifications

Configuration	Type	Ind. wire gauge size (AWG)	Width range (in.)	Rating range (amperes)	Comments
Standard flexible links for medium-duty application (cont'd)					
	FBSWC	30	3	1,300 – 2,350	Same construction as SWC with different hole configuration
	FBSWC	30	3	1,300 – 2,350	Same construction as SWC with different hole configuration
	FBSWC	30	3	1,300 – 2,350	Same construction as SWC with different hole configuration
	FBSWC	30	3	1,300 – 2,350	Same construction as SWC with different hole configuration
	FBSWC	30	2–4	600–1,850	Same construction as SWC with different hole configuration
	FBSWD	30	3¾–4¾	1600–2,100	4-hole transformer link
	FBSWC	30	3	1,300–2,100	1- to 4-hole transformer link
	FBSWD	30	3¾–4¾		1- to 4-hole transformer link
	FBSWD	30	3¾–4¾	1,600–2,100	2- to 4-hole transformer link
	FBSWD	30	3¾–4¾	1,600–2,100	3- to 4-hole transformer link
	FBSWE	30	3	1,400–1,600	6- to 4-hole transformer link
	FBSWF	30	3¾–4¾	1,700–2,300	6- to 4-hole transformer link
	FBSWE	30	3	1,400–1,600	6-hole transformer link
	FBSWF	30	3¾–4¾	1,700–2,300	6-hole transformer link

Technical specifications

Technical specifications

Configuration	Type	Ind. wire gauge size (AWG)	Width range (in.)	Rating range (amperes)	Comments
Large transformer links					
	FBLTL	30	6-6 3/8	2,500-4,000*	4-hole transformer link
	FBLTL	30	6-6 3/8	2,500-4,000*	4- to 6-hole transformer link
	FBLTL	30	6-6 3/8	2,500-4,000*	4- to 6-hole transformer link
	FBLTL	30	6-6 3/8	2,500-4,000*	6-hole transformer link
	FBLTL	30	6-6 3/8	2,500-4,000*	6-hole transformer link
	FBLTL	30	6-6 3/8	2,500-4,000*	6-hole transformer link

* For ampacity over 2,500 please contact your inside sale representative

Miscellaneous configurations and shapes

The following sketches represent the most popular configurations and shapes. For other non-standard flexible links and/or dimensions, send us a copy of your drawing with your specific requirements so that we can design and build the flexible connectors to your exact specifications.

