


CO1 Series

100 A 120/240 V; combination with or without breaker

Product specifications

- Conductor range (line and load): 6–1/0 AWG
- Aluminum tunnel type connectors for both load and line sides
- For overhead installation
- For underground installation, gutter option must be ordered (G)
- With factory-installed neutral conductor
- Suitable for 120/240 V single-phase service entrance for residential locations, mobile homes, trailers, temporary services, recreational parks and other commercial locations
- All units shipped complete with breaker will be supplied with either Siemens type Q (QP) OR GE type THQL (THHQL)
- Bottom compartment has provision for 2 pole circuit breaker (max 100 A) 10 Ka breakers (22 kA breaker where indicated HI) Siemens (QP, QPH), Eaton (BR), GE (TQL). Only SQD (CHOM) breakers will fit units with suffix SD.
- Supplied with screw type rings
- Weatherproof Type 3R enclosure



	Cat. no.	Type	Description	Dimensions (in.)			Weight each	
				H	W	D	lb	kg
4 Jaw								
CO1	CO1	Overhead	Provision for 2 pole 10 kA rated circuit breaker	23½	8¼	4¾	15	6.8
	CO1-G	Underground	Provision for 2 pole 10 kA rated circuit breaker, complete with gutter	23½	8¼	4¾	15	6.8
	CO1-5V	Overhead	Provision for 2 pole 10 kA rated circuit breaker, comes with 5th jaw	23½	8¼	4¾	15	6.8
	CO1-60	Overhead	Comes complete with 2 pole 60 A 10 kA rated circuit breaker	23½	8¼	4¾	15	6.8
	CO1-60HI	Overhead	Comes complete with 2 pole 60 A 22 kA rated circuit breaker	23½	8¼	4¾	15	6.8
	CO1-70	Overhead	Comes complete with 2 pole 70 A 10 kA rated circuit breaker	23½	8¼	4¾	15	6.8
	CO1-100	Overhead	Comes complete with 2 pole 100 A 10 kA rated circuit breaker	23½	8¼	4¾	15	6.8
	CO1-100G	Underground	Comes complete with 2 pole 100 A 10 kA rated circuit breaker, complete with gutter	23½	8¼	4¾	15	6.8
	CO1-100HI	Overhead	Comes complete with 2 pole 100 A 22 kA rated circuit breaker	23½	8¼	4¾	15	6.8
	CO1-100HI-G	Underground	Comes complete with 2 pole 100 A 22 kA rated circuit breaker, complete with gutter	23½	8¼	4¾	15	6.8
	CO1-SD	Overhead	Provision for Square D type QO 2 pole 10 kA rated circuit breaker	23½	8¼	4¾	15	6.8
	CO1-SD-G	Underground	Provision for Square D type QO 2 pole 10 kA rated circuit breaker, complete with gutter	23½	8¼	4¾	15	6.8



Diagrams

